

ALDEBARAN 4000A X SERIE



TYPE	ALDEBARAN 4000A X1 33 Wh	ALDEBARAN 4000A X1 66 Wh	ALDEBARAN 4000A X2 66 Wh	ALDEBARAN 4000A X2 99 Wh
Effekt	12 W	12 W	22 W	22 W
Lysstrøm ca.	1.200 lm	1.200 lm	2.200 lm	2.200 lm
Lystid ca.	Fuld/svag ydelse: 2½ h / 16 h	Fuld/svag ydelse: 5 h / 32 h	Fuld/svag ydelse: 3 h / 20 h	Fuld/svag ydelse: 4½ h / 30 h
Lysgiver	LED-Array-Teknologi	LED-Array-Teknologi	LED-Array-Teknologi	LED-Array-Teknologi
CRI	>70	>70	>70	>70
Lysfarve ca.	5000 °K	5000 °K	5000 °K	5000 °K
Akkumulator	LI-ION 1 x 4 celler, kapacitet ca. 33 Wh	LI-ION 2 x 4 celler, kapacitet ca. 66 Wh	LI-ION 2 x 4 celler, kapacitet ca. 66 Wh	LI-ION 3 x 4 celler, kapacitet ca. 99 Wh
Ladetid ca.	3 h	3 h	3 h	4,5 h
Ladeapparat	Ladeapparat til LI-ION Akkumulator Eurostecker 100-240 V AC Udgang max. 16.8 V. 2 A			
Tilladt driftstemp.	-20 °C til +40 °C	-20 °C til +40 °C	-20 °C til +40 °C	-20 °C til +40 °C
Tilladt ladetemp.	0 °C til +40 °C	0 °C til +40 °C	0 °C til +40 °C	0 °C til +40 °C
Dimension L x B x H)	267 x 120 x 145 mm	267 x 120 x 145 mm	385 x 120 x 145 mm	385 x 120 x 145 mm
Vægt ca.	1,05 kg	1,25 kg	1,6 kg	1,8 kg
Beskyttelsesniveau	IP54	IP54	IP54	IP54
Art.-Nr.:	1440800020	1440800022	1440800021	1440800023